

VH64C PP Double Sided Tape



PRODUCT DESCRIPTION

VH64C is a polypropylene base double-sided tape with a synthetic hot melt adhesive. Excellent adhesion to all surfaces and good adaptability on different surface shapes. Easy and clean removal. Transparent cast PP backing with bisilicone paper liner.



APPLICATION INFORMATION

- Uses include permanent or temporary carpet laying, miscellaneous industrial splicing and mounting applications, fixing, assembling, retail displays, etc.



PHYSICAL PROPERTIES

| | | | |
|------------------------|-------|----------------------|---------------------------------------|
| Total Thickness | 125µm | Adhesive Type | Synthetic Rubber + Hydrocarbon Resins |
| Film Thickness | 50µm | Peel Adhesion | 10N/cm |



AVAILABLE SIZES & COLOURS

* Tolerances: Thickness +/- 2µm; Width +/- 1mm

| CODE | SIZE | ROLLS / CARTON |
|----------|------------|----------------|
| A7573312 | 12mm x 33m | 96 |
| A7573319 | 19mm x 33m | 60 |
| A7573325 | 25mm x 33m | 48 |
| A7573338 | 38mm x 33m | 24 |
| A7573350 | 50mm x 33m | 24 |



STORAGE & TEMPERATURE CONDITIONS

Storage Tape performance is guaranteed within the first 12 months. Product must be kept in its original box and in a dry atmosphere away from direct sunlight.

Note: The following technical information and data should be considered representative or typical only.