

# N°220 Kraft Tape



## PRODUCT DESCRIPTION

No. 220 is constructed from high-quality kraft paper backing with silicone coating and a hot-melt pressure sensitive adhesive. Displaying strong adhesion and holding power, high tensile strength, resistance to curling and protection against various weather conditions (water proofing). Ideal for a multitude of applications.



## APPLICATION INFORMATION

- Sustainable alternative to plastic packaging tape, it is used in sealing corrugated cardboard boxes (virgin and recycled), sealing paper and woven bags, and enhancing projects by sticking seams and covering diverse boards.
- General packaging purposes, including sealing and bundling requirements.
- Hand tearable for ease of use.
- Also available in Printed "Fragile" Kraft Tape.



## PHYSICAL PROPERTIES

<b>Total Thickness</b>	120 microns	<b>Elongation</b>	1.5% – 3%
<b>Tensile Strength</b>	90N/25mm	<b>Peeling Adhesion</b>	20N/25mm
<b>Adhesive Type</b>	Hot Melt Pressure Sensitive Adhesive	<b>Backing Colour</b>	70g/m2 Kraft Paper Natural Kraft



## AVAILABLE SIZES & COLOURS

\* Tolerances: Thickness +/- 5um; Width +/- 1mm

<b>Standard Width</b>	48mm
<b>Core Size</b>	76mm (3 inch)
<b>Standard Length</b>	50m



## STORAGE & TEMPERATURE CONDITIONS

<b>Storage</b>	Tape performance is guaranteed within the first 12 months. Product must be kept in its original box and in a dry atmosphere away from direct sunlight.
<b>Service Temp</b>	-5°C – 60°C

Note: The following technical information and data should be considered representative or typical only.